

## 4 WAY ACTIVE SPLITTER

The Videosys 4-way Active Splitter is designed to efficiently divide UHF or IF signals while maintaining low insertion loss.

The unit is highly versatile, offering multiple configurations for DC pass-through and connector types to suit various applications.

Depending on the chosen setup, the splitter can be powered directly via Port 1 or through an external power supply, which can be provided separately.



## Specifications

Frequency Pass	50MHz - 950MHz	MAX DC Current	1 AMP
Through Loss	0dB $\pm$ 2dB	Current Consumption	120mA
Port to Port Isolation	+20db	Connector	BNC 75 Ohm Female
Return Loss	+10db	Dimensions	116mm x 66mm x 26mm
DC Passing Options	Input on Port 1 only	Mounting Dimensions	105mm x 57mm
Supply Voltage	12-48 V dc	Weight	400 grams
		RoSH/WEEE Compliant	YES

T: +44 (0)1293 541 200

E: [sales@videosys.tv](mailto:sales@videosys.tv)

W: [videosys.tv](http://videosys.tv)

[vbantennas.com](http://vbantennas.com)

The information contained in this document is the property of VideoSys Broadcast Ltd. This document and the information contained herein is provided for evaluation purposes only and is subject to change without notice. VideoSys Broadcast Ltd assumes no responsibility for errors that might appear in this document and gives no representations or warranties as to the accuracy of the information contained herein, including but not limited to the suitability and performances of the product or its intended application.